


General Notes

1. All work shall conform to the latest edition of the "Standard Specifications for Public Works Construction" and supplements thereto (APWA/AGC, "Green Book"). unless specifically noted otherwise.
2. All work shall conform to these Standard Plans, the Landscape Standard Plans, Arboricultural & Landscape Standards and Specifications, the Water Division Standard Plans and City Ordinances.
3. The contractor shall notify the Public Works Department at (714) 536-5431 at least 48 hours prior to beginning any work.
4. Working / Inspection hours are between 7:00 A.M. and 4:00 P.M. Monday through Friday, excluding Sundays and holidays. Any other hours to be approved prior to start of work. These hours may be subject to further limitations by Traffic Control requirements.
5. All work within public right-of-way or easements require an encroachment permit be obtained from the Public Works Department prior to the start of work..
6. The contractor shall be responsible for providing all testing required by the City.
7. The contractor shall keep a signed set of approved plans and a copy of the encroachment or grading permit on the job site during working operations.
8. All work shall comply with conditions established by the California Regional Water Quality Control Board and the City.
9. The contractor shall comply with all applicable federal, state and local safety requirements.
10. The contractor shall restore or replace in kind all existing improvements disturbed during construction including, but not limited to paving, utilities, street striping, landscaping and signs.
11. All work performed shall be guaranteed for a one year period.
12. One sack slurry backfill shall be used for all trench crossings of streets and all trenches within alleys.
13. Survey monuments or accessories to the same (tie points) shall be preserved, referenced and/or replaced pursuant to Section 8771 of the Business and Professions Code, of the State of California. Existing Survey monuments and their accessories in danger of being disturbed, covered, damaged or otherwise obliterated shall have a Corner Record filed with the Orange County Surveyor and the Local Agency prior to construction. In addition a Corner Record shall be filed with the Orange County Surveyor's office and the Local Agency prior to the the certificate of completion (Public Works Inspector's sign off) if the character of the monument or accessory to the same has been affected.
14. Temporary monuments set to establish lines of control, ownership, easements subdivision or tract boundaries or set as a direct reference to the same shall not be accepted. Permanent monuments which comply with Section 8772, of the Business and professions code shall be required prior to grading activities. A copy of the Corner Record or Record of Survey, shall be submitted to the Public Works Inspector prior to approval of grading activities.
15. All USA markings shall be removed within 24 hours of completion of the work.

APPROVED:

  
CITY ENGINEER

CITY OF HUNTINGTON BEACH

DEPARTMENT OF PUBLIC WORKS



REVISION DATE: May 2008

GENERAL NOTES

STANDARD PLAN  
100  
1 of 4