

ALLEY SECTION

| R/W* | ALLEY LOCATION |
|------|---------------------|
| 20' | RESIDENTIAL |
| 24' | DOWNTOWN COMMERCIAL |
| 30' | COMMERCIAL |


PLAN

*AS DETERMINED BY THE CITY ENGINEER
 NOTES:


- ① THICKNESS OF IMPROVEMENT TO BE DETERMINED BY SOIL TEST. MINIMUM SECTION 0.33' A.C. OVER 0.5' A.B.
- ② 2" X 8" REDWOOD HEADER WITH 2" X 3" X 18" D.F. STAKES, 36" O.C. SHALL BE USED FOR PAVEMENT EDGE EACH SIDE OF ALLEY.
- ③ WEAKENED PLANE OR QUICK JOINT, 20' O.C. MIN. IN ALLEY GUTTER SECTION.
- ④ CONSTRUCT 4" MIN. FULL WIDTH SIDEWALK WHEN PARKWAY IS LESS THAN 10' WIDE. SEE STANDARD PLAN 207 FOR PARKWAY AND SIDEWALK DETAILS.
- ⑤ 2 - 1/2" DIA. SMOOTH BARS, 2' LONG, 12" FROM EDGES AND 3" FROM BOTTOM OF ALLEY GUTTER.
- ⑥ 5' MINIMUM CLEARANCE FROM TOP OF 'X' TO ANY ABOVE-GROUND OBSTACLE (I.E., SIGN, POLE, TREE, ETC.). FOR ANY WATER APPURTENANCE SEE WATER STANDARD PLANS.

GENERAL NOTES:

- 1. ALLEYS SHALL NOT RECEIVE STREET DRAINAGE.
- 2. BACK OF ALLEY APPROACH CAN BE DEPRESSED A MAXIMUM OF 4" UPON APPROVAL BY THE CITY ENGINEER.
- 3. FOR ALLEY APPROACH DETAILS SEE STD. PLAN 210.

APPROVED:

 CITY ENGINEER

CITY OF HUNTINGTON BEACH
 DEPARTMENT OF PUBLIC WORKS



REVISION DATE: May 2008

ALLEY SECTION

STANDARD PLAN
 107
 2 of 3