



SPECIFICATION FOR LOCATION OF DRIVEWAYS:

1. 'W'=26' MINIMUM TO 45' MAXIMUM WIDTH. UNLESS OTHERWISE DETERMINED BY THE CITY ENGINEER.
2. TOTAL DRIVEWAY WIDTHS SHALL NOT EXCEED 70% OF THE FRONTAGE.
3. THE SAME PARCEL SHALL HAVE 22' MINIMUM OF FULL HEIGHT CURB BETWEEN DRIVEWAYS.
4. ALL PLANNED DRIVEWAY OPENINGS SHALL BE SUBMITTED TO THE DEPARTMENT OF PUBLIC WORKS, ENGINEERING DIVISION, FOR REVIEW AND APPROVAL. THE NUMBER OF DRIVEWAY OPENINGS SHALL BE NO MORE THAN ARE NEEDED TO ADEQUATELY SERVE THE PARCEL.
5. SEE STD. PLAN 211, SHEET 1 of 2, FOR DIMENSION AND SECTION DETAILS.

APPROVED:

CITY ENGINEER

REVISION DATE: May 2008

CITY OF HUNTINGTON BEACH

DEPARTMENT OF PUBLIC WORKS



COMMERCIAL AND INDUSTRIAL DRIVE APPROACH

STANDARD PLAN  
211  
2 of 2