

GENERAL NOTES: (CONT.)

7. SIGN POST ANCHOR

ROADSIDE SIGNS: DRIVE SIGN POST ANCHOR INTO GROUND APPROXIMATELY 30"
(DEPENDING ON LOCAL SOIL CONDITIONS).

MEDIAN SIGNS: SET SIGN POST ANCHOR INTO GROUND APPROXIMATELY
(STAMPED CONC) 6" BELOW FINISHED SURFACE. TOP OF ANCHOR SHOULD
PROTRUDE APPROXIMATELY 3" ABOVE FINISHED SURFACE.
VOID BETWEEN PATTERNED CONCRETE AND SIGN POST
SHALL BE FILLED WITH GROUT.

(LANDSCAPED) DRIVE SIGN POST ANCHOR INTO GROUND APPROXIMATELY
1'-6", LEAVING APPROXIMATELY 3" EXPOSED ABOVE GROUND
FOR CONNECTION (RIVETED).

SIGN POST INSERT SIGN POST AND RIVET IN PLACE WITH TWO (2) 5/16"
ANCHOR UNIVERSAL HEAD DRIVE RIVETS, ONE PLACED FACING DIRECTION
OF TRAVEL AND ONE OPPOSITE.

SIGNS ALL REGULATORY, WARNING, CONSTRUCTION AND GUIDE SIGNS
SHALL CONFORM TO THE LATEST STATE OF CALIFORNIA
MANUAL ON TRAFFIC CONTROL DEVICES SIGN SPECIFICATIONS
UNLESS NOTED OTHERWISE ON PLANS. SIGN SIZE SHALL BE
THE STANDARD SIZE SHOWN IN THE SIGN SPECIFICATIONS
UNLESS SHOWN OTHERWISE ON THE PLANS.

APPROVED:


TRANSPORTATION MANAGER

CITY OF HUNTINGTON BEACH

DEPARTMENT OF PUBLIC WORKS



REVISION DATE: 6/23/08

STREET SIGN ASSEMBLY

STANDARD PLAN

401

3 of 3